

Specifications

Name	Shurtape 155206 - AF 100 Silver- 2 1/2" X 60 Yards, Aluminum Foil Tape
Brand	Shurtape
Gemaire Item Number	AF100-2.5
Manufacturer Product Number	155206
SKU - PIM Number	1.37147E+12
ERP Number	108420
UPC	40074019416
Unit of Measure	EA
Weight	2.4
Length	5.4 Inches (In)
Width	5.4 Inches (In)
Height	2.5 Inches (In)
Hazardous Material	No
EPA Cert Required	No
Country of Origin	USA
Adhesion Strength	64 oz./in
Application Temperature	260°F to to20°F (127°C to to29°C)
Shelf Life	1 Year
Storage Temperature	Tape should be stored in its original packaging in a cool, dry area away from direct sunlight
UV Resistant	No
Tensile Strength	25 lb/in
Application	Joining And Sealing Class 1 Flex Duct And Fiberglass Duct Board
Approvals	UL 181A-P/B- FX
Color	Silver
Composition	Foil backing, acrylic adhesive, lined
Functions	UL 181 A-P/B-FX Listed aluminum foil HVAC tape for joining and sealing joints, connections and seams on rigid fiberglass duct board and flexible air duct. A tape that "does it all," AF 100 is engineered to form airtight bonds on joints and seams in application temperatures ranging from -20 F to 260 F and in humid conditions.
Maximum Temperature	260°F (126.6°C)
Performance Temperature	-20°F to 260°F (-28.8°C to 126.6°C)
Size	2.5" x 180'
Standards	UL Listed
Thickness	4.2 mil

Type	Foil
LEED Certified	Yes
UL Listed	Yes
UL Recognized	Yes
GEM - Case Quantity	